

K124 Cable Datasheet

SC, L1B 2p, open

Signal cable for CSM Out module, open cable end

Description

The signal cables are manufactured specifically for CSM. Highly durable wires are used, which are characterized by a high interference resistance and a good signal quality.

Temperature

The temperature range specified for the main cable, excluding connectors, is -40 to 80 °C. The temperature range specified for the connectors may vary depending on the type (e.g. LEMO B connector: -55 to 250 °C; D-Sub: -55 to 105 °C; Banana: -40 to 80 °C; LEMO Redel: -50 to 150 °C).

Main Cable Diameter


5.5 mm

Bending Radius

4 x Diameter (permanently installed)


Connectors

A	L1B	2-pole	Code: A	male
B	open			




Variants

Item No.	Cable Name	Length
ART0201187	K124-0200	2 m
	I1: 0.2 m	
ART0201190	K124-0400	4 m
	I1: 0.2 m	
ART0201188	K124-0500	5 m
	I1: 0.2 m	
ART0201189	K124-1000	10 m
	I1: 0.2 m	



Picture similar to actual product

Overview



Pinning

Con. A Pin	Signal	Cable Wire Color
1	VOUT+	white
2	VOUT-	brown
Housing	Cable shield	-



CSM GmbH

Raiffeisenstr. 36
70794 Filderstadt
Germany

Technical Questions:
www.csm.de/service-and-support

Sales Contact:
www.vector.com/contact

Part of the Vector Group



All trademarks mentioned are property of their respective owners.
Specifications are subject to change without notice.
CANopen® and CIA® are registered community trademarks of CAN in Automation e.V.
EtherCAT® is registered trademark and patented technology,
licensed by Beckhoff Automation GmbH, Germany.