

K200 Cable Datasheet

PC, L0B 5p, B

Power supply cable for UniCAN 2

Description

The signal cables are manufactured specifically for CSM. Highly durable wires are used, which are characterized by a high interference resistance and a good signal quality.

Temperature

The temperature range specified for the main cable, excluding connectors, is -30 to 150 °C. The temperature range specified for the connectors may vary depending on the type (e.g. LEMO B connector: -55 to 250 °C; D-Sub: -55 to 105 °C; Banana: -40 to 80 °C; LEMO Redel: -50 to 150 °C).

Main Cable Diameter

5.6 mm

Bending Radius

5 x Diameter (permanently installed)

Connectors


A	L0B	5-pole	Code: G	male
B	3x B	1-pole		male

A:




Variants

Item No.	Cable Name	Length
ART0650050	K200-0200	2 m
	I1: 1.8 m I2: 0.2 m	



Picture similar to actual product

Overview



Pinning

Con. A Pin	Signal	Cable Wire Color	Con. B Pin
1	Power +	red	red
2	Power GND	black	black
5	K15	grey	yellow
Housing	Cable shield	-	-
3, 4 n.c.	-	-	-



CSM GmbH

Raiffeisenstr. 36
70794 Filderstadt
Germany

Technical Questions:
www.csm.de/service-and-support

Sales Contact:
www.vector.com/contact

Part of the Vector Group



All trademarks mentioned are property of their respective owners.
Specifications are subject to change without notice.
CANopen® and CIA® are registered community trademarks of CAN in Automation e.V.
EtherCAT® is registered trademark and patented technology,
licensed by Beckhoff Automation GmbH, Germany.