

K71 Cable Datasheet

CC, L0B 5p, L0B 5p

Extension cable with Lemo 0B 5p (Code G)

Description

The signal cables are manufactured specifically for CSM. Highly durable wires are used, which are characterized by a high interference resistance and a good signal quality.

Temperature

The temperature range specified for the main cable, excluding connectors, is -30 to 150 °C. The temperature range specified for the connectors may vary depending on the type (e.g. LEMO B connector: -55 to 250 °C; D-Sub: -55 to 105 °C; Banana: -40 to 80 °C; LEMO Redel: -50 to 150 °C).

Main Cable Diameter


5.6 mm

Bending Radius

5 x Diameter (permanently installed)


Connectors

A	L0B	5-pole	Code: G	female
B	L0B	5-pole	Code: G	female




Variants

Item No.	Cable Name	Length
ART0201059	K71-0020	0.2 m



Picture similar to actual product

Overview



Pinning

Con. A Pin	Signal	Cable Wire Color	Con. B Pin
1	Power +	red	1
2	Power GND	black	2
3	CAN_H	yellow	3
4	CAN_L	green	4
5	CAN_GND	grey	5
Housing	Cable shield	-	Housing



CSM GmbH

Raiffeisenstr. 36
70794 Filderstadt
Germany

Technical Questions:
www.csm.de/service-and-support

Sales Contact:
www.vector.com/contact

Part of the Vector Group



All trademarks mentioned are property of their respective owners.
Specifications are subject to change without notice.
CANopen® and CIA® are registered community trademarks of CAN in Automation e.V.
EtherCAT® is registered trademark and patented technology,
licensed by Beckhoff Automation GmbH, Germany.