

K73 Cable Datasheet

IC, L0B 5p, DS 9p/ B

Cable between CAN socket/measurement module and CAN interface; incl. 1 m power supply line

Description

The signal cables are manufactured specifically for CSM. Highly durable wires are used, which are characterized by a high interference resistance and a good signal quality.

Temperature

The temperature range specified for the main cable, excluding connectors, is -30 to 150 °C. The temperature range specified for the connectors may vary depending on the type (e.g. LEMO B connector: -55 to 250 °C; D-Sub: -55 to 105 °C; Banana: -40 to 80 °C; LEMO Redel: -50 to 150 °C).

Main Cable Diameter



5.6 mm

Bending Radius

5 x Diameter (permanently installed)

Connectors

| Code | Connector Type | Poles | Code | Gender |
|------|----------------|--------|---------|--------|
| A | L0B | 5-pole | Code: G | male |
| B | DS | 9-pole | | female |
| C | 2x B | 1-pole | | male |




Variants

| Item No. | Cable Name | Length |
|------------|---------------------------|--------|
| ART0201051 | K73-0250 | 2.5 m |
| | I1: 1.5 m I2: 1 m I3: 1 m | |
| ART0201074 | K73-0300 | 3 m |
| | I1: 2 m I2: 1 m I3: 1 m | |
| ART0201071 | K73-0500 | 5 m |
| | I1: 4 m I2: 1 m I3: 1 m | |
| ART0201524 | K73-1000 | 10 m |
| | I1: 9 m I2: 1 m I3: 1 m | |
| ART0201545 | K73-2000 | 20 m |
| | I1: 19 m I2: 1 m I3: 1 m | |



Picture similar to actual product

Overview



Pinning

| Con. A Pin | Signal | Cable Wire Color | Con. B Pin | Con. C Pin |
|---------------|--------------|---------------------|--------------------|---------------|
| 1 | Power + | red | - | red |
| 2 | Power GND | black | - | black |
| 3 | CAN_H | yellow | 7 | - |
| 4 | CAN_L | green | 2 | - |
| 5 | CAN_GND | grey | 3 | - |
| Housing | Cable shield | - | 5 + Housing | - |
| - | - | - | 1, 4, 6, 8, 9 n.c. | - |



CSM GmbH

Raiffeisenstr. 36
70794 Filderstadt
Germany

Technical Questions:
www.csm.de/service-and-support

Sales Contact:
www.vector.com/contact

Part of the Vector Group



All trademarks mentioned are property of their respective owners.
Specifications are subject to change without notice.
CANopen® and CIA® are registered community trademarks of CAN in Automation e.V.
EtherCAT® is registered trademark and patented technology,
licensed by Beckhoff Automation GmbH, Germany.